

TECHNICAL CHARACTERISTICS TEKNİK ÖZELLİKLER				
SIN VISAGE				
TEST TYPES / TEST TİPİ	ASPECT / KRİTER	NORM	UNİT / BİRİM	STANDART TEST
WEIGHT / AĞIRLIK		590±45	g/m ²	ISO 2286-2
THICKNESS / KALINLIK		1,15±0,10	mm	ISO 2286-3
TENSILE STRENGTH / KOPMA	ACROSS / EN	>200	N	ISO 1421
	ALONG / BOY	>400	N	ISO 1421
TEAR STRENGTH / YIRTIKMA	ACROSS / EN	>25	N	ISO 4674-1
	ALONG / BOY	>25	N	ISO 4674-1
ELONGATION AT BREAK / UZAMA	ACROSS / EN	260±20%	%	ISO 1421
	ALONG / BOY	75±20%	%	ISO 1421
ADHESION / YAPISMA		>40	N	ISO 2411
MARTINDALE - ABRASION		>50.000	RUB(12kPa)	ISO 5470-2
COLOR FASTNESS TO RUBBING / SÜRTÜNME RENK HASLIĞI	DRY / KURU	≥4	GS	ISO 105X12
	WET / ISLAK	≥4	GS	ISO 105X12
LIGHT FASTNESS / IŞIK HASLIĞI	LIGHT COLORS / AÇIK RENKLER	≥4	BW	ISO 105B02
	DARK COLORS / KOYU RENKLER	≥5	BW	ISO 105B02
COMPOSITION - İÇERİK				
VINYL / URETHANE TOP COAT				
BACKING - ZEMİN				
POLYESTER				
Flokser Tekstil San. ve Tic. A.Ş. Hadımköy Mah. Ürgüplü Cad. No:7 34555 Arnavutköy / İSTANBUL _TÜRKİYE				
PHONE /TELEFON +90 212 866 49 00			FAX / FAKS +90 212 771 32 37	
EMAIL: info@flokser.com.tr / musterihizmetleri@flokser.com.tr				
www.flokser.com.tr				