

TOLEDO

TECHNICAL CHARACTERISTICS / TEKNİK ÖZELLİKLER

COMPOSITION/İÇERİK	BACKING/ZEMİN
VINYL / URETHANE TOP COAT VİNİL / POLİÜRETAN YÜZEY	%100 POLYESTER

TEST TYPES / TEST TİPİ	ASPECT / KRİTER	NORM	UNIT / BİRİM	STANDART TEST
WEIGHT / AĞIRLIK		650 ± 40	g / m ²	ISO 2286-2
MARTINDALE - ABRASION / AŞINMA DAYANIMI		> 50.000	RUB	ISO 5470-2
TEAR STRENGTH / YIRTILMA DİRENCİ	ACROSS / EN	> 25	N	ISO 4674-1
	ALONG / BOY	> 25	N	ISO 4674-1
TENSILE STRENGTH / KOPMA DİRENCİ	ACROSS / EN	> 180	N	ISO 1421
	ALONG / BOY	> 400	N	ISO 1421
ELONGATION AT BREAK / KOPMA ANINDAKİ UZAMA	ACROSS / EN	250 ± 20%	%	ISO 1421
	ALONG / BOY	75 ± 20%	%	ISO 1421
COLOR FASTNESS TO RUBBING / SÜRTÜNME RENK HASLIĞI	DRY / KURU	≥ 4	GS	ISO 105-X12
	WET / ISLAK	≥ 4	GS	ISO 105-X12
LIGHT FASTNESS / IŞIK HASLIĞI	LIGHT COLORS / AÇIK RENKLER	≥ 4	BW	ISO 105-B02
	DARK COLORS / KOYU RENKLER	≥ 5	BW	ISO 105-B02



MODASER TEKSTİL

Yukarı Dudullu Mah. Bostancı Yolu Üzeri Keyap Çarş. E1 Blok No: 73 34775 Ümraniye - İstanbul

+90 216 313 4213
+90 530 118 6872

info@modaser.com.tr

www.modaser.com.tr

f in @ / exclusivesmartfabrics

